KEYSTONE COMPAC® III STRAIGHT SPLIT





Granite City Blend

The Compac[®] III Straight Split's shape allows for tight radius curves and vertical core alignments. This wall can do it all with vertical or battered setback construction options. With triangular-shaped receiving holes, construction adjustments are simplified. Natural stone appearance and rich colors complement any setting.





40 Sq Ft on Pallet 40 Pcs on Pallet Pallet Weight: 3,100 lbs

8" x 18" x 12"













Adobe Blend

Corner blocks are used to build the pier. A cap provides the finishing touch as well as additional lighting possibilites.

8" Corner

Builds Per Pallet: One: 27" x 27" x 64" H pier Two: 27" x 27" x 32" H piers



8" x 18" x 9'

32 Sq Ft on Pallet

32 Pcs on Pallet Pallet Weight: 2,509 lbs

Maximum exposed height for gravity walls is 36" under ideal conditions. Soil type, crest slopes and surcharges will decrease max exposed height for gravity walls. Consult a professional engineer to determine site and specific colors.

NOTE: All walls over 2' in height or as required by local code should be designed by a licensed professional engineer. All measurements are nominal. Variance in square footage or linear footage coverage can be up to 5% depending on joint width. The possible occurrence of efflorescence does not affect the structural integrity of the product. Efflorescence is a normal occurrence in concrete products and will dissipate with normal weathering. The use of concrete as a base or setting bed may increase the possibility of efflorescence.