

# STONE RIDGE



*Chesapeake Blend*



*Granite City Blend*


Multi-sized rectangular shapes. Slightly textured riven surface. Slightly chamfered edge. Can be combined with Stone Ridge XL.




## 3-Piece



**A**  
4 1/2" x 9" x 2 3/8"








**B**  
9" x 9" x 2 3/8"



**C**  
9" x 13 1/2" x 2 3/8"

110 Sq Ft on Pallet  
240 Pcs on Pallet | A- 130 B- 60 C- 50  
Pallet Weight: 2,950 lbs




\*Premium Color  
\*\*Deluxe Color


### INSTALLATION GUIDELINES: SAND

After excavation, compact the sub grade and install a woven separation fabric if needed. Spread and compact a base of clean, dense graded aggregate (road base). Typical compacted base thickness is 4-6" for pedestrian applications. Pavers are set on a loosely screened 1" bed of graded, clean concrete sand. Maintain a joint size of 1/16" – 3/16". When pavers are set, compact paving stones into sand with mechanical plate vibrator. Joint sand may be spread over paving stones during compaction. Installed pavers should be set 1/8" to 1/4" above final elevations to compensate for any potential settlement. Spread clean dry sand over surface and broom sweep to fill joints. Run vibrator one final time after filling joints.

### NICOLOCK PAVING STONE 1"- 3 1/8" THICK



### CROSS-SECTION OF TYPICAL INSTALLATION



**NOTE:** All measurements are nominal. Variance in square footage or linear footage coverage can be up to 5% depending on joint width. The possible occurrence of efflorescence does not affect the structural integrity of the product. Efflorescence is a normal occurrence in concrete products and will dissipate with normal weathering. The use of concrete as a base or setting bed may increase the possibility of efflorescence.

**CAUTION:** Always use a plate compactor with a pad when installing any textured paving stone.